

Application Recommendation

ArmourColor Escenta Finish

1 General Requirements

All substrates to receive ArmourColor Escenta shall be sound, crack-free, dustfree, flat, and smooth (equivalent to a drywall level 5) and free of surface contaminants and defects.

2 New Drywall Application Recommendation

Primer: Apply 2 coats of BaseColor Matt and allow to dry. Thin down 1st coat with 20% water as new drywall is a porous surface.

Finish: Apply 1 coat of ArmourColor Escenta to match approved project sample. Allow to dry prior to sealing.

Sealer: Apply 1 coat of Clearseal Gloss.

*note - when applying any ArmourColor products by roller, use a 1/4" nap quality roller cover.

3 Alternative Substrate Applications

Brick, Block, CMU, & Precast: Prepare as to receive a high-sheen paint coating (level 5). Apply 2 coats of BaseColor Matt and allow to dry. Thin down 1st coat with 20% water if prepared surface is porous.

Previously Painted: Test for bond and load bearing strength and prepare to conform to the general requirements (level 5). For glossy paints lightly sand surface to remove surface luster. This recommendation is for water based paint systems only. Apply 1 coat of BaseColor Matt.

MDF Panels: Apply 2 coats of Sherwin Williams Preprite Wall & Wood Primer B49W2, or equivalent oil-based wood primer to all six sides of the panels and allow to dry. All MDF panels are to be at least 3/4" in thickness. Apply 1 coat of BaseColor Matt.

Build quality is the responsibility of the General Contractor.

For other substrates please contact the Technical Dept. at: technical@armourcoat.co.uk

Whilst every attempt has been made to ensure the accuracy and reliability of the information contained in this document, the information should not be relied upon as a substitute for formal advice. Armourcoat Ltd, its employees and agents will not be liable for any loss or damage, of any kind, arising out of or in connection with the use of this document. Please refer to the company disclaimer for further details.

SAT AR12 0609©

Armourcoat Limited

4330 Production Court
North Las Vegas NV 89115
Tel: 702 644 0601
Fax: 702 644 0554
Email: sales@usa.armourcoat.com

web: www.usa.armourcoat.com