



Substrate Preparation

Polished Plaster with AntiCrack Base

1 General Requirements

All substrates to receive Armourcoat Polished Plasters shall be sound, crack-free, dust-free, flat, smooth (equivalent to a drywall level 4), and free of surface contaminants and defects.

2 Recommended Substrates

Regular GWB: No taping and jointing required, except where code designates a fire-rated wall, in which case a level 1 finish must be achieved on the drywall prior to the application of AntiCrack.

Brick, Block, CMU, & Precast: Apply National Gypsum Kal-Kote Base Coat plaster system, or equivalent, and allow to cure to conform to the general requirements.

Build quality is the responsibility of the General Contractor.

For other substrates please contact the Technical Dept. at: technical@armourcoat.co.uk

Whilst every attempt has been made to ensure the accuracy and reliability of the information contained in this document, the information should not be relied upon as a substitute for formal advice. Armourcoat Ltd, its employees and agents will not be liable for any loss or damage, of any kind, arising out of or in connection with the use of this document. Please refer to the company disclaimer for further details.

SAT 0609©

Armourcoat Limited
4330 Production Court
North Las Vegas NV 89115
Tel: 702 644 0601
Fax: 702 644 0554
Email: sales@usa.armourcoat.com

web: www.usa.armourcoat.com